3 AA BATTERIES

XPP-5420B, XPP-5420G

INTRINSICALLY SAFE PERMISSIBLE FLASHLIGHT





© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

CLASS I DIV 1

INTRINSICALLY SAFE PERMISSIBLE FLASHLIGHT

3 AA BATTERIES (not included)

ITEM NUMBER/UPC

- XPP-5420B, UPC 0 17398 80092 1 - XPP-5420G, UPC 0 17398 80091 4

MARKET APPLICATIONS

Hazardous work environments, industrial

CERTIFICATIONS

- ETLus, CE, UKCA, MSHA

CASE MATERIAL

- Engineered polymer

FLASHLIGHT LUMENS/RUNTIME

- 160L, 14 hrs. runtime

CANDELA

- 7.500

BEAM DISTANCE - 180 m

WATER RATING

ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.0 in (178 mm)
- HANDLE DIAMETER: 1.1 in x 1.5 in (28 mm x 38 mm)
- HEAD DIAMETER: 1.8 in (46 mm)
- WEIGHT: 7.3 oz (207 g)

POWER SOURCE

- AA batteries (not included)

WARRANTY

Limited lifetime

WHAT'S INCLUDED

- Flashlight
 - Removable lanyard
 - Instruction manual



XPP-5420B Bayco Products, Inc. 640 S. Sanden Blvd. Wylie, TX 75098

Permissible Nightstick 5420 Flashlight MSHA APPROVAL No. 20-A130001-0 TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY WARNINGS: 1) MSHA approved for use with three AA Duracell Type PC1500. Energizer Type EN91, and Energizer Type L91 batteries only. 2) Replace the batteries in fresh air only and replace all batteries at the same time. Do not mix batteries from different manufacturers or of different types. 3) Energizer Lithium (Type L91) batteries are to be replaced by a qualified technician only. 4) The Model Nightstick 5420 must not be opened in areas where permissibility is required.



UK

ČÀ

CE

CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135C CLASS I ZONE 0 IIC T3 CLASS II ZONE 20 IIIC T135C -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AA Alkaline

Bayco Products, Inc. XPP-5420G 640 S. Sanden Blvd. Wylie, TX 75098

Permissible Nightstick 5420 Flashlight MSHA APPROVAL No. 20-A130001-0 TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY WARNINGS: 1) MSHA approved for use with three AA Duracell Type PC1500, Energizer Type EV91, and Energizer Type L91 batteries only. 2) Replace the batteries in fresh air only and replace all batteries at the same time. Do not mix batteries from different manufacturers or of different types. 3) Energizer Lithium (Type L91) batteries are to be replaced by a qualified 4) The Model Nightstick 5420 must not be opened in areas where permissibility is required. (ETI) CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135C CLASS I ZONE 0 IIC T3



CERTIFIED €D.

CLASS II ZONE 20 IIIC T135C -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AA Alkaline

